

VALVOLA A SFERA PER CONTATORI, ATTACCHI M. PER CALOTTA CON FORO DI PIOMBAGGIO-FARFALLA ALLUMINIO.

BALL VALVE FOR METERS CONNECTION M. FOR SWIVEL UNION NUT WITH PLUMBING HOLE-ALUMINIUM BUTTERFLY HANDLE.

ART. 195/A

IMPIEGHI - USES

L'Airaga Rubinetterie S.P.A produce e collauda le valvole a sfera art. 195/A adottando un sistema di qualità secondo le norme UNI EN ISO 9001-2008. Vengono utilizzate principalmente in applicazioni civili ed industriali che utilizzano liquidi compatibili non corrosivi, aria compressa e acqua. Il presente articolo è esente da marcatura CE in base all'Art.3 Par.3 della Direttiva 97/23/CE PED.

Airaga Rubinetterie spa produces and tests ball valves range 195 according to a quality system UNI EN ISO 9001:2008. They are used mainly in : civil and industrial systems with non corrosive fluids, compressed air and water . This item is CE marking-free according to Art.3 Par.3. with reference 97/23/CE PED directive.



MATERIALI E CARATTERISTICHE - MATERIALS AND FEATURES



Corpo e manico: stampati a caldo da barra EN12165 CW617N, nichelati.
Premistoppa e asta di comando: lavorati da barra EN12164 CW614N.
Sfera: stampata-fusa-tornita da barra EN12165 CW617N, diamantata e cromata a spessore.
Anello ferma asta: lavorato da barra EN12164 CW614N.
Guarnizioni di tenuta sfera: P. T. F. E. vergine - durezza 55-60 shore D.
Guarnizione asta: P. T. F. E. vergine - durezza 55-60 shore D.
Farfalla di manovra: pressofuse o fuse in lega di alluminio UNI 5076-74 sabbiate e rivestite con vernici epossidiche.
Calotta: lavorati da barra EN12164 CW614N, nichelata.
Vite: UNI 5739 - acciaio zincato.
Attacchi filettati: filettature UNI ISO 228/1 (DIN 259).
Sigillante per filettature: adesivo anaerobico tipo "Loctite".
Trattamento esterno valvola: superficie nichelata brillante.

Body and sleeve: hot moulded from EN12165 CW617N bar, nickel-plated.
Gland and push rod: worked from EN12164 CW614N bar.
Ball: moulded, melted or turned from EN12165 CW617N bar, diamond and chrome plated.
Rod-stopping ring: worked from EN12164 CW614N bar.
Ball gaskets: P. T. F. E. virgin - hardness 55-60 shore D.
Rod gasket: P. T. F. E. virgin - hardness 55-60 shore D.
Butterfly handle: die cast or melted in aluminium alloy UNI 5076-74, sandblasted and coated with epoxidic paints.
Swivel: worked from EN12164 CW614N bar, nickel-plated.
Screw: UNI 5739 - galvanized steel.
Threaded connections: UNI ISO 228/1 (DIN 259) threads.
Seal for threads: "Loctite" type anaerobic adhesive.
External treatment: brilliant, nickel plated surface.

CONDIZIONI DI ESERCIZIO - WORKING CONDITIONS

Working temperature: service limit from -20° C +120° C.

Temperatura di esercizio: limite di servizio da -20° C a +120° C.



ART.	195/A				
DN x DN1 e pass. mm	1/2" M x 3/4" B (15)	3/4" M x 3/4" B (15)	1" M x 3/4" B (15)	3/4" M x 1" B (20)	1" M x 1" B (20)
L mm	65,5	69	69,5	73,5	76,5
B mm	40	40	40	52	52
F mm	11	15	14	13	15,5
CH1 mm	32	32	32	37	37
CH2 mm	22	27	25	27	34
A mm	50	50	50	50	50
Peso (Weight) g.	220	230	240	350	380

* L'Airaga Rubinetterie SpA si riserva il diritto di apportare qualsiasi modifica di forma, dimensione e materiale sui propri prodotti.
* Airaga Rubinetterie Spa has the right to modify any shape, dimension and material on our products.